



Model IB Bucket Traps

(VAC - 250 PSIG)
Inverted Bucket Design

Features

- Available in 1/2", 3/4", 1", 1-1/4", 1-1/2", 2" and 2-1/2" sizes to meet nearly every industrial and process application
- High strength cast iron bodies
- Low maintenance - tolerates dirty steam - for maximum service life and reliability
- Immediate condensate discharge at saturated steam temperature
- Meets MIL Spec WW T 696

Description

Designed for extended service and low maintenance with medium and high pressure steam. Mepco Bucket Traps feature an inverted bucket design with corrosion resistant stainless parts for optimal performance with blast coils, laundry equipment, hot water heaters, steam kettles and a broad range of industrial and process applications.

Operation

Key to the reliability of a Mepco Bucket trap is that the trap is selected for the actual pressure differential of your application, and the valve seat and plug are in the top, away from the dirt and debris that collects in the trap body. A trap being used for a greater differential than its rating will not open. Conversely, a trap with a rating which exceeds the differential will operate at a reduced capacity.

Initially primed to create a water seal with the bucket in a down (fully open) position, air and water enter the trap through the inlet tube. Air is vented from a small orifice in the top of the bucket, while condensate flows out from under the bucket. When steam enters the trap, it fills the bucket, causing it to become buoyant, overcoming the weight of the bucket, and rising to "snap" the plug into the seat. The trap stays fully shut until sufficient steam has condensed to allow the bucket to immediately drop, and return to its full open state.

Mepco offers seven models in 20 capacities. Using the table on the reverse, specify the Mepco trap which delivers the most efficient energy saving operation and lowest maintenance cost.



Engineering Specifications: Capacities (Gross)

DIFFERENTIAL PRESSURE (PSIG)

lbs. condensate per hour

Model	Pipe Size	PMO	Orifice	1/4	1	5	10	15	20	30	60	70	80	100	125	150	180	200	225	250	
IB00	1/2"	20	3/16	140	272	460	560	646	698	-	-	-	-	-	-	-	-	-	-	-	-
	and 80	1/8		48	112	200	310	370	420	510	640	662	690	-	-	-	-	-	-	-	-
	3/4"	125	7/64	24	56	92	150	200	262	350	490	530	570	642	685	-	-	-	-	-	-
	150	#38		20	54	75	112	153	205	275	385	415	442	482	545	572	-	-	-	-	-
IB11	1/2"	15	1/4	192	452	835	952	1062	-	-	-	-	-	-	-	-	-	-	-	-	-
	and 30	3/16		125	310	545	672	775	882	1000	-	-	-	-	-	-	-	-	-	-	-
	3/4"	70	5/32	72	170	185	440	500	590	715	905	952	-	-	-	-	-	-	-	-	-
	and 125	1/8		56	135	225	342	396	465	565	715	762	805	862	955	-	-	-	-	-	-
IB12	1/2"	15	5/16	350	825	1610	1920	2110	-	-	-	-	-	-	-	-	-	-	-	-	-
	and 30	1/4		285	510	950	1385	1640	1800	2060	-	-	-	-	-	-	-	-	-	-	-
	3/4"	70	3/16	198	425	790	950	1125	1270	1510	2010	2210	-	-	-	-	-	-	-	-	-
	and 125	5/32		110	310	565	690	820	910	1075	1450	1555	1660	1810	2020	-	-	-	-	-	-
IB13	3/4"	15	1/2	955	1880	2910	3525	3900	-	-	-	-	-	-	-	-	-	-	-	-	-
	and 30	3/8		500	1420	2310	2700	3320	3510	4000	-	-	-	-	-	-	-	-	-	-	-
	1"	60	5/16	350	950	1745	2050	2525	2830	3140	4440	-	-	-	-	-	-	-	-	-	-
	80	9/32		310	740	1355	1600	1960	2220	2450	3500	3825	4025	-	-	-	-	-	-	-	-
IB14	1"	15	5/8	1410	2920	4825	5810	6500	-	-	-	-	-	-	-	-	-	-	-	-	-
	and 30	1/2		955	2255	3710	4750	5220	6010	6810	-	-	-	-	-	-	-	-	-	-	-
	1-1/4"	60	3/8	510	1775	2960	3560	4000	4725	5420	6810	-	-	-	-	-	-	-	-	-	-
	80	11/32		390	1570	2525	2925	3225	3525	4440	5775	6000	6420	-	-	-	-	-	-	-	-
IB15	1-1/4"	15	3/4	2060	4170	7625	9020	10000	-	-	-	-	-	-	-	-	-	-	-	-	-
	and 30	9/16		925	2920	5220	6430	7725	8525	9825	-	-	-	-	-	-	-	-	-	-	-
	1-1/2"	60	7/16	600	2220	3810	5025	6025	6625	7625	9525	-	-	-	-	-	-	-	-	-	-
	and 100	3/8		510	1720	3030	3620	4525	5220	6110	8525	9225	9725	10420	-	-	-	-	-	-	-
IB16	2"	15	1-1/16	4060	8420	14525	17350	19200	-	-	-	-	-	-	-	-	-	-	-	-	-
	and 25	7/8		2090	5500	10000	12950	15620	18525	-	-	-	-	-	-	-	-	-	-	-	-
	2-1/2"	40	3/4	1905	4510	8220	10625	12810	15000	18000	-	-	-	-	-	-	-	-	-	-	-
	60	5/8		1460	3520	6910	8720	10620	12110	14270	19825	-	-	-	-	-	-	-	-	-	-
	80	9/16		1270	3100	6000	7620	9330	10620	12500	17325	18320	19000	-	-	-	-	-	-	-	-
	125	1/2		1065	2620	5000	6410	7820	8900	10500	14525	15420	16330	18100	20000	-	-	-	-	-	-
	180	7/16		915	2220	4190	5550	6660	7525	9250	12420	13330	14200	15800	17500	18500	20000	-	-	-	
	250	3/8		590	1820	3410	4525	5410	6110	7500	10125	10825	11510	12830	14300	15610	16900	17500	18500	19000	

Dimensions

MODEL #	IB00	IB11	IB12	IB13	IB14	IB15	IB16
Pipe Size	1/2"- 3/4"	1/2"- 3/4"- 1"	1/2" - 3/4"-1"	3/4" - 1 "	*1" - 1-1/4"	*1-1/4"-1-1/2"-2"	2" - 2-1/2"
Prime Plug	1/4"	1/4"	1/2"	3/4"	1"	1-1/2"	2"
A Face to Face	5"	5"	6-1/2"	8-1/2"	9"	10-1/4"	13
B Height	6"	7"	9-1/16"	12-1/2"	14"	16-1/4"	21-5/16
C C.L.to bottom	3-1/4"	4-1/4"	5-3/8"	7-1/32"	8"	8-1/4"	11"
Weight	5#	6#	15#	27-1/2#	44#	71#	131#
Max Op. Press.	150	250	250	250	250	250	250

*Face bushed to Size

List of Materials

Part	Material
Cap & Body	ASTM A48 CI 30
Gasket	Compressed Non Asbestos
Bolt/Nut	Grade 5 or 7
Valve/Valve Seat	Stainless Steel
Retainer	Stainless Steel
Lever	Stainless Steel
Bucket	Stainless Steel

